


Fiberglass mesh reinforced fibreglass mat

PRODUCT DESCRIPTION

Fiberglass mesh reinforced fibreglass mat is a fiberglass mat reinforced with fiberglass mesh. The fiberglass mesh gives very strong tensile strength in both longitudinal direction and lateral direction to the composite mat. The tensile strength is adjustable, so the reinforced fiberglass mat can be produced according to the tensile strength requirement of the customers. It is widely used in bituminous membrane as substrate material, because of its high tensile strength, it is also used for paving, pipe wrapping.



CHARACTERISTICS

- ◆ High tensile strength, high tear strength, orrosion resistance
- ◆ Tensile strength can be adjusted freely as per customer demand.
- ◆ Easy soakage of bitumen

TECHNICAL DATA

Item No.	Unit	GF80-5X5-FB	GF90-6X6-FB	GF110-6X6-FQ	GF140-8X8-FJ
Area Weight	g/m2	80	90	110	140
Width	mm	1000	1000	1000	1000
Length	m	1350	1250	1250	1000
Tensile Strength MD	N/5CM	400	500	500	550
Tensile Strength CD	N/5CM	200	250	450	600
Roll Diameter	mm	780	780	780	780
Core Diameter	mm	76	76	76	76
Moisture	%	<2.5	<2.5	<2.5	<2.5

Remark: Other specification can be customized as per customers' demand.

PACKING

Every roll in plastic film, 114rolls/40' HQ without pallet.

STORAGE

This product should be stored in a dry, ventilated and rainproof place, with temperatures from 5°C to 35°C and humidity between 35% and 65%. It is recommended to be kept in intact package when not used to avoid damp.

Version #: No.201911

Address: No.20 Jiangjun Ave., Nanjing, P.R. China

URL: www.fiberglassnonwoven.com

E-mail: sales@njefg.com

Tel.: 0086 25 52270147 / 58321911

Fax: 0086 25 58321442

WhatsApp: 0086 18851651909